Pro Charging Systems, LLC, 1551 Heil Quaker Blvd., LaVergne, TN 37086-3539 S

Weight

Per Unit

3.0 lbs

5.0 lbs

7.0 lbs

Size

Per Unit

3.0" x 4.5" x 6.5"

3.0" x 6.5" x 7.25"

3.0" x 6.5" x 10.25"

Sales Support: 866.755.8399

Float Stage

YES

YES

YES

Maintenance

Reverse

Polarity

YES

YES

YES

12V-36V www.dualpro.com

Battery

System

12V, 24V

12V



## Features of Recreation Series Battery Chargers:

- Approved for Wet Cell and Absorbed Glass Mat (AGM) batteries
- Designed for use in fresh and salt water
- Dependable, rugged construction and waterproof
- Independent outputs and fully automatic
- Battery maintenance mode

Description

One 6 AMP Bank

Two 6 AMP Banks

Three 6 AMP Banks

• Two year warranty

Model

RS1

RS2

RS3

- DC charge cables = 5ft and AC power cord = 3ft
- C E approved and meets ISO 8846 Marine standards
- Models available to charge 12-36V systems
- LED lights indicate "Each Battery's" state of charge
- Reverse polarity protected and no installation restrictions

Total

Output

6 Amps

12 Amps

18 Amps

- Ignition protected (US Coast Guard 33 CFR 183.410)
- FCC 15 Parts A and B Interference Compliant

Battery Ch	arging Systems Desig	gned for <mark>E</mark>	veryday Ap	oplications

- Affordable, Reliable and Safe
- TROUBLE FREE—Just Plug It In and Forget It!
- Join Over 750,000 of Our Satisfied Customers!
- Wide Variety of Applications

## May be used in many types of everyday applications including: Bass Boats, Runabouts, Pontoons, Other Watercraft, Automobiles, ATVs, Golf Carts...

Go Charge battery chargers are an affordable, reliable and safe battery charging system designed for everyday use. The system is engineered for users who need a charging system on an occasional basis and may not want or need the capabilities of a heavier duty and higher amperage product. The system delivers superior value to customers.

## Go Char









Independent

Outputs

YES

YES

YES



## Recreation SERIES PRO Charging Systems









Two 6 Amp Banks Model RS2



One 6 Amp Bank Model RS1

Model	Description	Total Output	Weight Per Unit	Size Per Unit	Reverse Polarity	Float Stage Maintenance	Independent Outputs	Battery System
RS1	One 6 AMP Bank	6 Amps	3.0 lbs	3.0″ x 4.5″ x 6.5″	YES	YES	YES	12V
RS2	Two 6 AMP Banks	12 Amps	5.0 lbs	3.0" x 6.5" x 7.25"	YES	YES	YES	12V, 24V
RS3	Three 6 AMP Banks	18 Amps	7.0 lbs	3.0" x 6.5" x 10.25"	YES	YES	YES	12V-36V

Pro Charging Systems, LLC, 1551 Heil Quaker Blvd., LaVergne, TN 37086-3539 Sales Support: 866.755.8399

www.dualpro.com